

ENGINEERING
TOMORROW



Fact sheet | VACON® 3000 Enclosed Drive

A modular and configurable cabinet-built drive delivering superior performance

Ready to run
**medium-
voltage
drives**

Power rating

12-pulse Diode Front End (DFE) enclosed drives

AC drive type	Continuous rating (variable torque)		Low overload rating 110% (constant torque)		High overload rating 150% (constant torque)		Cabinet dimensions HxWxD [mm]
	Continuous current I _{th} [A]	Continuous power [kVA]	Continuous current I _L [A]	Continuous power [kVA]	Continuous current I _H [A]	Continuous power [kVA]	
Nominal voltage 3300 V							
VACON3000-ED-12-0425-03	425	2430	386	2209	283	1620	2130x2400x1000
VACON3000-ED-12-0640-03	640	3660	582	3327	427	2440	2130x2600x1000
VACON3000-ED-12-0820-03	820	4690	745	4264	547	3127	2130x3400x1000
VACON3000-ED-12-1230-03	1230	7030	1118	6391	650	4680	2130x3800x1000
Nominal voltage 4160 V							
VACON3000-ED-12-0340-04	340	2450	309	2227	227	1633	2130x2400x1000
VACON3000-ED-12-0510-04	510	3670	464	3336	340	2447	2130x2600x1000
VACON3000-ED-12-0650-04	650	4680	591	4255	433	3120	2130x3400x1000
VACON3000-ED-12-0980-04	980	7060	891	6418	650	4680	2130x3800x1000

Active Front End (AFE) enclosed drives

AC drive type	Continuous rating (variable torque)		Low overload rating 110% (constant torque)		High overload rating 150% (constant torque)		Cabinet dimensions HxWxD [mm]
	Continuous current I _{th} [A]	Continuous power [kVA]	Continuous current I _L [A]	Continuous power [kVA]	Continuous current I _H [A]	Continuous power [kVA]	
Nominal voltage 3300 V							
VACON3000-ED-4Q-0425-03	425	2430	386	2209	283	1620	2130x2400x1000
VACON3000-ED-4Q-0640-03	640	3660	582	3327	427	2440	2130x2600x1000
VACON3000-ED-4Q-0820-03	820	4690	745	4264	547	3127	2130x3800x1000
VACON3000-ED-4Q-1230-03	1230	7030	1118	6391	650	4680	2130x4400x1000
Nominal voltage 4160 V							
VACON3000-ED-4Q-0340-04	340	2450	309	2227	227	1633	2130x2400x1000
VACON3000-ED-4Q-0510-04	510	3670	464	3336	340	2447	2130x2600x1000
VACON3000-ED-4Q-0650-04	650	4680	591	4255	433	3120	2130x3800x1000
VACON3000-ED-4Q-0980-04	980	7060	891	6418	650	4680	2130x4400x1000

Active Front End (AFE) transformerless enclosed drives

AC drive type	Continuous rating (variable torque)		Low overload rating 110% (constant torque)		High overload rating 150% (constant torque)		Cabinet dimensions HxWxD [mm]
	Continuous current I _{th} [A]	Continuous power [kVA]	Continuous current I _L [A]	Continuous power [kVA]	Continuous current I _H [A]	Continuous power [kVA]	
Nominal voltage 3300 V							
VACON3000-ED-4Q-0425-03+PICM	425	2430	386	2209	283	1620	2130x3000x1000
VACON3000-ED-4Q-0640-03+PICM	640	3660	582	3327	427	2440	2130x3400x1000
VACON3000-ED-4Q-0820-03+PICM	820	4690	745	4264	547	3127	2130x5200x1000
VACON3000-ED-4Q-1230-03+PICM	1230	7030	1118	6391	650	4680	2130x6000x1000
Nominal voltage 4160 V							
VACON3000-ED-4Q-0340-04+PICM	340	2450	309	2227	227	1633	2130x3000x1000
VACON3000-ED-4Q-0510-04+PICM	510	3670	464	3336	340	2447	2130x3400x1000
VACON3000-ED-4Q-0650-04+PICM	650	4680	591	4255	433	3120	2130x5200x1000
VACON3000-ED-4Q-0980-04+PICM	980	7060	891	6418	650	4680	2130x6000x1000



VACON® 3000 Enclosed Drive

Options

VACON® 3000 Enclosed Drive

AFE supply type

+PHSI	High Source Impedance Please contact Danfoss Drives to check the source impedance specification.
--------------	---

+PICM	Common Mode Filter
--------------	--------------------

Functional safety

+QSTO	Safe Torque Off function, Cat 0 (EN 60204-1)
--------------	--

Dynamic braking

+DBC	Brake Chopper
-------------	---------------

Output filters

+PODU	dU/dt filter
--------------	--------------

+POSI	Sine wave filter
--------------	------------------

Grounding

+PGGG	Grounded heatsink, grounded bleeding resistor (Standard)
--------------	--

+PGGF	Grounded heatsink, floating bleeding resistor
--------------	---

Approvals

+GAMA	Marine approved construction
--------------	------------------------------

+GAUL	cUL-listed version
--------------	--------------------

Board & function	Option code & slots	Loose option
OPT-B1 6 x D1/DO	+S_B1 C, D, E	OPT-B1-V
OPT-B2 2 x RO + Thermistor	+S_B2 C, D, E	OPT-B2-V
OPT-B4 1 x A1, 2 x AO	+S_B4 C, D, E	OPT-B4-V
OPT-B5 3 x RO	+S_B5 C, D, E	OPT-B5-V
OPT-B9 3 x RO	+S_B9 C, D, E	OPT-B9-V
OPT-BF 1 x AO, 1 x DO, 1 x RO	+S_BF C, D, E	OPT-BF-V
OPT-BH Temperature measurement (non-ATEX) (1x, 2x, 3x PT100, PT1000, Ni1000, KTY84)	+S_BH C, D, E	OPT-BH-V

Protocol	Option code	Loose option
LonWorks	+S_C4	OPT-C4-V
RS232 Adapter	+S_D3	OPT-D3-V
PROFIBUS DP	+S_E3	OPT-E3-V
PROFIBUS DP with Sub-D9	+S_E5	OPT-E5-V
CANopen	+S_E6	OPT-E6-V
DeviceNet	+S_E7	OPT-E7-V
RS485 (Modbus/N2) with Sub-D9	+S_E8	OPT-E8-V
Advanced dual-port Ethernet	+S_EA	OPT-EA-V
EtherCAT	+S_EC	OPT-EC-V

Technical data

Topology	3-level neutral point clamped (NPC)	HV-IGBT
Drive capacity	3300 V	425 A, 3300 V, 2.4 MVA 640 A, 3300 V, 3.7 MVA 820 A, 3300 V, 4.7 MVA 1230 A, 3300 V, 7.0 MVA
	4160 V	340 A, 4160 V, 2.5 MVA 510 A, 4160 V, 3.7 MVA 650 A, 4160 V, 4.7 MVA 980 A, 4160 V, 7.1 MVA
Input voltage		3300 V, 3 phases $\pm 10\%$ 4160 V, 3 phases $\pm 10\%$
Input frequency		50 Hz $\pm 5\%$ (3300 V) or 60 Hz $\pm 5\%$ (4160 V)
Rectifier	Active Front End	AFE
	Diode Front End	12-pulse DFE
Input current THD	AFE	< 5 %
	12-pulse DFE	< 15 %
Power factor		> 0.95
Output voltage levels		3 (5 phase-to-phase)
Output frequency		0-120 Hz
Acceleration/deceleration time		0.1-3600 s
Grounding		Isolated neutral, resonant earthing, high resistive earthing or solid earthing (IEC61936-1). For operation in unearthed neutral systems without a dedicated transformer, contact Danfoss Drives.
Switching frequency		AFE: 1050 Hz (50 Hz) and 1260 Hz (60 Hz) INU: 900 Hz synchronous PWM
Motor control method	Asynchronous (induction) motor	U/f control Open loop control Indirect closed loop control Closed loop control
Communication		AI/O, DI/O, fieldbuses (e.g. PROFIBUS DPV1, DeviceNet), industrial Ethernet protocols (PROFINET IO and EtherNet IP™), VACON® PC tool
Main protective functions		Torque and power limit, current limit, overcurrent, overvoltage, undervoltage, loss of auxiliary power, loss of communication, ground fault detection, arc detection, leak detection
Efficiency	AFE + INU	> 97.5 %
	DFE + INU	> 98.5 %, excluding the input transformer
Temperature	Operational (<i>ambient</i>)	0 °C to +45 °C (+30 °F to +113 °F)
	Storage (<i>ambient</i>)	-40 °C to +70 °C (-40 °F to +158 °F); No liquid in heat sink under 0 °C (+32 °F)
	Enclosed drive inlet cooling liquid	0 °C to +38 °C (+32 °F to +100 °F). Lowest permitted cooling liquid temperature 2 °C (3.6 °F) above the dew point.
Relative humidity		< 95 % RH, non-condensation, non-corrosive
Cooling	Power module (<i>phase modules, rectifiers</i>)	Liquid cooled
	Chokes	Hybrid cooling (forced air cooled with air-to-liquid heat exchanger)
Standards		IEC **, cUL **, marine standards **

*For lower voltage operation, please contact Danfoss Drives

** certification pending

ENGINEERING
TOMORROW



Fact sheet | VACON® 3000 Enclosed Drive

A modular and configurable cabinet-built drive delivering superior performance

Ready to run
**medium-
voltage
drives**